



Spiromatic 90USA



Spiromatic 90USA is a simple but effective breathing apparatus (SCBA) for industrial and maritime environments having NIOSH approval for industrial use.

Spiromatic 90USA is built upon the proven and reliable plug-in regulator system, delivering Interspiro performance at a competitive price. The harness is equipped with padded shoulder straps and easy-to-adjust waist belt buckle.

The apparatus has a pressure gauge, warning whistle and optional extra air connection. The plug-in type regulator is durable and has proven functionality with high flow capacity maintaining the safety pressure also at an extreme rate of breathing and low cylinder pressures. The plug-in type design makes service and repairs easy to perform with short down time.

- Open back plate for good ventilation and low weight
- Easy to handle and adjustable cylinder strap
- Small and light warning whistle placed on chest
- Carrying handle integrated in backplate

- Well-proven and robust pneumatics
- Mask and breathing valve in a compact design

The Incurve USA SCBA is combined with the S-USA face mask and breathing valve presented under “Firefighting/Face Mask”, follow the below links for more information:

- [S-USA Ambient air hatch version](#)
- [S-USA First breath version](#)

Variants with airline connector also have a quick coupling between the breathing hose and the breathing valve. These variants only fit mask assemblies with quick coupling (qc) on the breathing valve.

Variants without airline connector have a threaded connection between the breathing hose and the breathing valve. these variants only fit mask assemblies not having a quick coupling (qc) on the breathing valve.

The Spiromatic 90USA SCBA variants exclude face mask, breathing valve and cylinder.

Technical specification

Air flow : 1350 l/min

Approval : NIOSH

Connection : DOT cylinders - 30-60 minutes

Connection (2) : Cylinder - CGA

Material : Heat resistant polymer backplate

Material (2) : Aramid reinforced Nylon

Standard : 42 CFR part 84

Warning : Pneumatic whistle

Weight with packaging : 3.1 kg (excl. mask & breathing valve)

Accept cookies from this site

This website uses cookies to to improve your experience on the site. By clicking accept, you agree to our [privacy_policy](#) and [cookie_policy](#).

- Do not accept cookies
- Only accept functional cookies
- Accept all cookies